



A look at Mapei from its humble beginnings as a small company on the outskirts of Milan to its current position as a world-leading multinational specialising in adhesives and chemical products for the building industry. 65 years ago, Mapei was just a small company on the outskirts of Milan.

The big change came when the company began concentrating its efforts on a specific market niche.

In Poland Mapei products are very popular, like in the UK. This was the reason we decided to keep a large range of their products in stock.



Ultracolorol

Fast setting and drying grout for 2 to 20 mm joints, available in 26 colours; does not produce efflorescence.

Application:

Interior and exterior grouting of all types of ceramic tiles on walls and

floors (double fired, single fired, klinker, porcelain, terracotta, etc.), glass mosaic, natural stone, concrete-framed glass blocks, etc. Easy to apply and finish. Ensures perfect colour evenness, does not produce surface efflorescence, dries rapidly, therefore floors and coverings are ready for traffic rapidly.

Suitable for grouting joints on external façades, balconies, terraces, swimming pools, bathrooms and kitchens. Particularly suitable for grouting floor joints of supermarkets, motorway services, restaurants, airports and public premises. Coverage depending on the size of the joint. Packaging 25 kg bags, 4x5 and 9x1 kg boxes depending on colour.



Kerapoxy

Two-component acid-resistant epoxy grout for joints over 3 mm. Available in 26 colours.

Application:

Interior and exterior grout for ceramic tiles and natural stones on floors and walls. Particularly suitable for grouting floors and walls

in the food industry, thermal water baths, tanks containing aggressive chemicals, work surfaces in kitchens, hospitals, supermarkets and in all environments where complete hygiene is required and resistance to most aggressive chemicals. Kerapoxy P is recommended for grouting large surfaces. Coverage depends on the size of the joint.



Keracolor

Cement based grout for joints up to 6 mm.

Applications:

Interior and exterior, smooth and low absorption grouting on walls and floors of all types of ceramic tiles (double fired, single fired, klinker, porcelain, terracotta, natural stone, granite, agglomerates etc.), glass and

marble mosaic, concrete-framed glass blocks, etc. Easy to apply and finish.

Suitable for grouting joints in swimming pools, bathrooms, kitchens and floors with particularly smooth and glossy surfaces.

Keracolor FF mixed with Fugolastic improves its final performance and achieves a high resistance even under severe conditions of use. Coverage depend on the size of the joint. Packaging 25 kg bags and 4x5 kg boxes depending on colour.



1Liquid polymeric additive for Keracolor FF and GG.

Applications:

Fugolastic is used instead of water for mixing Keracolor FF and GG cement based grouts in order to improve compactness and resistance to abrasion, and reduce porosity and water absorption.

Particularly suitable for grouting floors subject to heavy traffic, swimming pools, terraces, balconies and façades. N.B. Do not use Fugolastic with Keracolor FF or GG when grouting terracotta floors or very porous or rough surfaces. When grouting polished porcelain floors, make a preliminary test to verify whether it can be properly cleaned. Coverage depends on the size of the joint.